

Fast- Bond

ID: G1-FSTB
Version: 1
Edition: 1



PVA bonding agent

Description

Fast- Bond is a ready to use as a cement modifier.

Key functions

Fast- Bond is used as an Integral bonding agent and for cement-based mixes as tile adhesives, plaster, repair mortars and screeds.

Product properties*

Type:	Formulated copolymer emulsion
colour:	White
Density:	1.01 kg/l

* Values are valid at ambient temperature of 23°C and at 55% relative humidity using standard water/powder ratio

Application instructions

Dosage

Fast- Bond is added in a rate of 2 to 4 litres per 50 kg cement.

Note: The above dosage rates are a guide only. It is the contractor's / user's responsibility to ensure that all the materials to be used are compatible and further that they meet the design criteria and specification requirements.

Mixing

Preferably in a pan mixer but hand batching is permissible when the total weight of the mix is less than 25kg. Charge the mixer with the required quantity of sand and cement and pour in the required quantity of Fast-Bond and mix for 2 minutes only to avoid excessive air entrainment. Add water carefully until the required consistency is achieved.

Curing

Correct curing of Fast- Bond modified mixes is important. Moisture cure for at least 1 day and then allow to dry out slowly.

Cleaning

Clean tools with water before hardening. Hardened material can only be removed mechanically.

Watch-points

- Always use fresh cement and well-graded aggregate free of excessive fines.
- Keep mixing time to a minimum.
- Modified mixes are deceptive in their workability. Avoid using excess water.
- Trowelling should proceed with the work. Do not over trowel and avoid re-trowelling.
- Protect from too rapid drying out prior to trowelling.

Storage and shelf life

Fast- Bond has a minimum shelf life of 12 months when stored in good warehouse conditions away from direct sunlight in ambient temperature between 5°C and 35°C.

For ambient temperatures outside this range consult Arki for advice.

Packaging

Fast- Bond is supplied in 20 L containers.

Safety precautions

Fast- Bond is a non-flammable material.

Fast- Bond is not classified as hazardous material under current legislations.

Fast- Bond may cause irritation to the skin and eyes. Therefore, unnecessary contact with the product is to be avoided and suitable gloves and goggles must be worn.

Do not dispose into water or soil. Dispose the material according to local regulations.

Accidental contact of Fast- Bond to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, seek medical advice.

For further information, refer to the material safety data sheet.

Technical support

Arki provides assistance to its customers and gives site support, consultations and technical advice on concrete repair, surface preparation and treatment, tile adhesive and tile grout selection and tile installation techniques.

Additional Arki products

Arki produces high quality products intended for use in construction activity, among these products:

- Concrete Admixtures
- Concrete repair materials.
- Mould release agents and curing compounds.
- Waterproofing materials.
- Flooring systems.
- Tile adhesives and tile grouts
- Protective coatings.

Product Quality

All Arki products are manufactured under a quality management system independently certified to conform to the requirements of the international standards.

