

Cleaner for ceramic tiles and cementitious floors

Description

Arki-Clean is an acidic martial designed to penetrate below the surface to remove tile grout haze, light cement smears, mineral deposits, rust stains and efflorescence. This product is also effective for the removal of most hard water stains, lime deposits and soap scum.

Key functions

- Removal of excess mortar and tile grout from ceramic and porcelain tiles.
- Removal of cement stains from ceramic and porcelain tiles.
- Removal of efflorescence (salt-like deposits).

Product properties

Appearance:	Water-like liquid
Colour:	Straw
Specific Gravity:	1.09 at 23°C
pH:	1.0
Flash point:	Non-flammable
Coverage rate:	~5m ² / litre without dilution

Directions for use

Mix 1 part of Arki-Clean with 3 parts of water. stronger solution may be used depending on nature of the task.

Apply Arki-Clean with a clean sponge or synthetic mop and let to dwell 1 to 2 minutes. Care should be taken to keep the work areas wet at all times. Do not allow solution to dry on surface. Scrub the area with a nylon bristle brush to loosen dirt, soiling and cement haze. Rinse thoroughly the floor with clean water and a clean mop to remove the dirty solution.

Important Notes:

Allow newly grouted installations to cure a minimum of 10 days.

This product is not intended for use on polished marble, coloured cement tiles, metallic glazed tile and metals.

Safety precautions

Arki-Clean is an acid-based corrosive substance and should be handled with care.

Avoid inhalation of vapour. It should not be swallowed or allowed to come into contact with skin. Suitable protective goggles and rubber gloves should be worn.

Accidental contact of Arki-Clean to the eyes, rinse immediately with plenty of water and seek medical advice.

In case of contact with skin, wash off immediately with soap and water. In the event of prolonged irritation, seek medical advice.

If swallowed, seek immediately medical attention. Do not induce vomiting.

For further information refer to the material safety data sheet.

Packaging

3.75 and 20 Litre jerrycans.

Storage and shelf life

Arki-Clean has a shelf life of 12 months when stored in sealed original containers. ^A

Technical support

Arki provides assistance to its customers and gives site support, consultations and technical advice on all aspects related to specifications and application methods of construction chemicals and building materials.

Additional Arki products

Arki produces high quality products intended for use in construction activity, among these products:

- Admixtures for concrete and mortar.
- Surface treatments and primers.
- Engineering grouts.
- Concrete repair and restoration systems.

- Industrial flooring systems.
- Protective coatings and linings.
- Waterproofing materials.
- Adhesives and tilling systems.
- Construction sealants and joint fillers.

Product Quality

All Arki products are manufactured under quality management system independently certified to conform to the requirements of the international standards.



P. O. Box 301100
Riyadh 11372, Saudi Arabia
Mobile: +966 54 7673235
e-mail: info@arkichem.com

Users should always refer to the most recent issue of the product technical data-sheet for the product concerned, copies of which will be supplied on request.
Arki products are guaranteed against defective materials and manufacture and are sold subject to Arki standard terms and conditions of sales.
Because the storage, handling and application of these products are beyond our control, we can accept no liability for the results obtained.